

DCP1005

Features

- + **Touch panel for cabin crew interaction**
 - + **Cabin telephone and internet control unit**
 - + **Displays telephone status and connections**
 - + **User management**
 - + **System maintenance interface**
 - + **Intuitive drag & drop controls**
 - + **MCDU interface**
-
- + 15 inch capacitive touch screen with laminated safety glass
 - + Satellite logon state indication
 - + Telephone features
 - + Connection overview and control
 - + Accept/transfer/redirect calls via drag & drop
 - + Bearer system capacity and state indication
 - + Router feature
 - + VIP mode
 - + Master internet switch
 - + Indication & control of LAN clients (connected smartphones, tablet computers, etc.)
 - + Hidden maintenance mode for IPX & DCP
 - + Electrical interfaces
 - + Temperature monitoring
 - + IPX & DCP Firmware upload control
 - + Lightweight browser



Mechanical dimensions

| | |
|--------|---------------------------------|
| length | 370 mm |
| height | 296 mm |
| depth | 80 mm (100 mm with disconnects) |
| weight | max. 4,9 kg |

Specifications

input voltage 115 V AC / 400 Hz

MTBF 8.000 OH

DCP1005 connections

- + 1 x Power input (115 V)
- + 1 x Sub-D: address configuration
- + 1 x ARINC 429 (DEMA9P): interface to satcom SDU
- + 1 x RS 232 (DEMA9S): serial interface
- + 1 x 10 BaseT, ethernet (RJ45): interface to IPX/PAPX